


Truck Valve V408NTA Tube to Male Pipe

Temperature Range: -30° to +250° F (-34.4° to +121.1° C)


Part No.	Hose I.D.	Pipe Thd	Flow	L	M	N
V408NTA-8-8	1/2	1/2	.328	3.28	1.15	1.19



Truck Valve V409F Flare to Male Pipe

Temperature Range: -30° to +250° F (-34.4° to +121.1° C)


Part No.	Hose I.D.	Pipe Thd	Flow	L	M	N
V409F-8-6	1/2	3/8	.406	3.07	1.31	1.00
V409F-8-8	1/2	1/2	.406	3.28	1.31	1.19
V409F-10-8	5/8	1/2	.500	3.47	1.50	1.25
V409F-12-8	3/4	1/2	.562	3.70	2.31	1.34



Truck Valve V410NTA Tube to Male Pipe

Temperature Range: -30° to +250° F (-34.4° to +121.1° C)


Part No.	Hose I.D.	Pipe Thd	Flow	L	M	N
V410NTA-8-8	1/2	1/2	.328	3.58	1.38	1.31



Truck Valve V412F Tube to Male Pipe

Temperature Range: -30° to +250° F (-34.4° to +121.1° C)

Part No.	Hose I.D.	Pipe Thd	Flow	L	M	N
V412F-10-8	5/8	1/2	.500	3.60	1.38	1.31



WARNING

This product can expose you to chemicals including Lead and Lead Compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov