



Additional Options:	Air Shift Installed
For Fluid Type:	Standard Hydraulic Fluids, Phosphate-ester
Weight:	70 lb (Max), 32 kg (Max)
Control Method:	n/a
Maximum Displacement:	6.4 inch ³ /rev, 105 cm ³ /rev
Radial Load Capacity:	n/a
Thru-Drive Capability:	No
Filter Included:	No
Media:	n/a
Mounting Option:	DIN, SAE
Maximum Flow Rate:	n/a
Shaft Type:	SAE, SAE "B" 13T
Direction of Rotation:	Counterclockwise, Clockwise, Bi-Rotational
Configuration:	Single
Pump Type:	Gear, Fixed
Maximum Operating Pressure:	2500 psi, 172 bar
Drain Option:	No
Minimum Fluid Temperature:	0 °F, -20 °C
Maximum Fluid Temperature:	80 °C, 180 °F
Port Connection:	NPT
Minimum Kinematic Viscosity:	50 SUS

Maximum Operating Speed:	2400 RPM
Sensor Type:	n/a
Charge Pump Included:	No
Energy Recovery Capability:	No
Maximum Noise Level:	n/a
Port Location:	Rear Ports
Operating Pressure:	up to 2500 psi, up to 172 bar
Flow Rate:	n/a
Displacement:	up to 105 cm ³ /rev, up to 6.4 inch ³ /rev
Circuit Path:	Open
Maximum Kinematic Viscosity:	7500 SUS
Port Type:	Tapered Thread
Product Type:	Hydraulic Pump Gear, Fixed Displacement, C102
Body Material:	Cast Iron
Seal Material:	Buna-N, TEFLON
Inlet Connection Size:	1-1/4 inch, NPT
Outlet Connection Size:	NPT 1 inch (Cylinder), NPT 1 inch (Tank-plugged)
Shaft Diameter:	7/8 inch
Rotation:	CCW
Additional Options:	n/a
Pressure Rating (psi):	2500 PSI
Configuration:	4-BOLT SQUARE
Displacement:	6.38 cu. in. / 104.5 cc